

MACHINE	PRO ECO 2			
DESCRIPTION	.150" X 62"			
PRODUCT	COLD ROLLED STEEL			
	HOT ROLLED PICKLED AND OILED STEEL			
	HOT ROLLED PICKLED DRY STEEL			
	GALVANIZED STEEL			
	GALVANNEAL STEEL			
	COLD ROLLED FULL HARD			
	ALUMINUM			
YIELD STRENGTH	0.150" @ 90 000 PSI			
MASTER COIL CAPACITY	MIN.	MAX.		
COIL WEIGHT		60 000		
THICKNESS	0.020	0.150		
WIDTH	5.000	62.000		
INT. DIAMETER	20.000	24.000		
OUT. DIAMETER	30.000	72.000		
SLITTING CAPACITY	0.020	0.080	0.120	0.150
50-60 KSI TENSILE STRENGTH	22	15	8	4
60-70 KSI TENSILE STRENGTH	18	12	7	3
70-80 KSI TENSILE STRENGTH	14	9	6	2
80-90 KSI TENSILE STRENGTH	10	6	5	2
CHARACTERISTICS	MATERIAL CAN BE PROCESSED WITH OFF-CUTS			
	ENTRY AND EXIT CROP SHEAR			
	PLEASE INQUIRE FOR SLITTING, SIDETRIMMING OR PACKAGING OUTSIDE SPECIFICATION			

SLITTING LIMITS	MIN.	MAX.
WIDTH	0.500	61.500
REQUIRED SCRAP	0.375	1.000