

<b>MACHINE</b>	SLITTER 5							
<b>DESCRIPTION</b>	3/8" X 72"							
<b>PRODUCT</b>	HOT ROLLED STEEL							
	HOT ROLLED PICKLED AND OILED STEEL							
	HOT ROLLED PICKLED DRY STEEL							
	GALVANIZED STEEL							
<b>YIELD STRENGTH</b>	0.375" @ 95 000 PSI							
<b>MASTER COIL CAPACITY</b>	<b>MIN.</b>	<b>MAX.</b>						
<b>COIL WEIGHT</b>		76 000						
<b>THICKNESS</b>	0.055	0.375						
<b>WIDTH</b>	23.000	72.000						
<b>INT. DIAMETER</b>	20.000	30.000						
<b>OUT. DIAMETER</b>	42.000	85.000						
<b>SLITTING CAPACITY @ 95 KSI</b>	<b>0.060</b>	<b>0.075</b>	<b>0.105</b>	<b>0.125</b>	<b>0.160</b>	<b>0.187</b>	<b>0.280</b>	<b>0.375</b>
<b>72"</b>	22	18	15	13	11	10	8	7
<b>60"</b>	20	16	13	12	11	9	7	6
<b>48"</b>	18	15	12	11	9	8	7	5
<b>36"</b>	16	14	11	10	8	7	6	5
<b>CARACTERISTICS</b>	1 SLITTING HEAD WITH 4 BRANCH SETUP CAPSTAN							
	OFF-LINE COIL BANDING STATION							
	SCRAP CHOPPERS							

<b>SLITTING LIMITS</b>	<b>MIN.</b>	<b>MAX.</b>
<b>WIDTH</b>	2.500	72.000
<b>REQUIRED SCRAP</b>	0.500	3.000